

Pressure Booster Pumps



Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		No. of Bathrooms	Tank Capacity	Pressure Range	Head in Meter								
	Kw	HP	Suc.	Del.				Discharge in LPH	3	6	9	12	15	18	21	25
LPBS 0502	0.37	0.50	25	25	1	2 Ltr Tank	1.5-3.0	2300	2100	1800	1600	1400	1200	900	700	0
LPBS 0524	0.37	0.50	25	25	2	24 Ltr Tank	1.5-5.0	3800	3500	3150	2800	2400	2000	1500	1000	0
LPBS 1024	0.75	1.00	25	25	3	24 Ltr Tank	1.5-5.0	4300	4000	3650	3300	2900	2500	2000	1500	900

Material of Construction

Impeller : SS
 Motor Body : Aluminum
 Shaft : Chrome Plated Shaft
 Pressure Tank : MS
 Float Switch

Features

- Withstand wide voltage fluctuation from 180 to 255 volts.
- Thermal overload protector (TOP) prevents motor burning.
- High quality aluminum body.
- Light weight pump for easy handling.

Applications

- Water supply for domestic use in Bungalows, Apartments, Hotels, Hospital, Farm house, etc.
- Useful in Home presser booster system, Lawn sprinklers.

OTHER PRODUCT RANGE



LYNN PUMPS PVT. LTD.

Corporate Office : 201, Freeway Trade Centre, Narol-Aslali Highway Narol, Ahmedabad. (Gujarat)

East Zone Office : First Floor, Opp. Samrat Pump, Bari Pahari, Transport Nagar, Alamganj, Patna. (Bihar)

E-MAIL : CRM@LYNNPUMPS.COM | WEB : WWW.LYNNPUMPS.COM

TOLL FREE : 18005729923, 18001206323

DOMESTIC SERIES WATER PUMPS



A PERFECT PUMPING MACHINE FOR YOUR PERFECT HOME



SELF PRIMING REGENERATIVE PUMPS



Scan QR Code To download app now

DOWNLOAD LYNN CARE APP FOR SERVICE & COMPLAIN



WWW.LYNNPUMPS.COM



DELTA (MAGIC SUCTION)



Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		Discharge in LPH	Head in Meter											
	Kw	HP	Suc.	Del.		6	9	12	15	18	21	24	27	30	33	36	39
Delta 05	0.37	0.50	15	15		1550	1400	1250	1150	1000	850	600	400	-	-	-	-
Delta 075	0.55	0.75	25	25		1950	1800	1650	1550	1400	1300	1150	950	800	-	-	-
Delta 100	0.75	1.00	25	25		2200	2000	1850	1700	1550	1350	1200	1000	850	750	500	200

Material of Construction

Impeller : H.T. Brass
 Casing : SS
 Motor Body : Aluminum Die Cast
 Shaft : Chrome Plated Shaft

Features

- Withstand wide voltage fluctuation from 180 to 255 volts.
- Self priming suction lift upto 7.5 meter.
- Thermal overload protector (TOP) prevents motor burning.
- High quality aluminium / Cast iron body.
- Light weight pump for easy handling.

Applications

- Water supply for domestic use in Bungalows, Appartments, Hotels, Hospital, Farm house, etc.
- Useful in Home presser booster system, Lawn sprinklers.

EVAN (V TYPE)



Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		Discharge in LPH	Head in Meter								
	Kw	HP	Suc.	Del.		9	15	18	21	24	28	32	36	40
EVAN 05	0.37	0.50	25	25		2600	2200	2000	1750	1550	1050	650	400	0
EVAN 10	0.75	1.00	25	25		2700	2300	2100	1850	1650	1300	850	650	450

Material of Construction

Impeller : H.T. Brass
 Casing : Casting
 Motor Body : Aluminum Die Cast
 Shaft : Chrome Plated Shaft

Features

- Withstand wide voltage fluctuation from 180 to 255 volts.
- Self priming suction lift upto 7.5 meter.
- Thermal overload protector (TOP) prevents motor burning.
- High quality aluminum / Cast iron body, Light weight pump.

Applications

- Water supply for domestic use in Bungalows, Apartments, Hotels, Hospital, Farm house, etc.
- Useful in Home presser booster system, Lawn sprinklers.

RIO (OPENWELL PUMP)



Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		Discharge in LPM	Head in Meter											
	Kw	HP	Suc.	Del.		6	9	10	12	14	16	18	20	22	24	26	28
RIO 05	0.37	0.50	25	25		170	160	150	130	110	85	60					
RIO 10	0.75	1.00	25	25				220	200	190	185	170	160	135	120	90	

Material of Construction

Motor Body : SS
 Armature : Copper

Features

- Withstand wide voltage fluctuation from 180 to 255 volts
- High quality Cast iron / SS body.

Applications

- Water supply for domestic use in Bungalows, Apartments, Hotels, Hospital, Farm house, etc.

COVE (NRV PUMP)



Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		Discharge in LPH	Head in Meter													
	Kw	HP	Suc.	Del.		6	9	12	15	18	21	24	28	30	36	40			
COVE MINI 05	0.37	0.50	25	25		1900	1600	1300	1050	800	600	450	250	0	0	0			
COVE 05	0.37	0.50	25	25		2700	2400	2100	1800	1450	1050	750	400	0	0	0			
COVE MINI 10	0.75	1.00	25	25		2750	2500	2150	1900	1550	1200	950	650	500	0	0			
COVE 10	0.75	1.00	25	25		3150	2900	2650	2350	2150	1950	1700	1450	1250	500	400			

Model Name	Kw	HP	Suc.	Del.	LPH	6	9	12	15	18	20	24	27	30	35	40	45	54
COVE 10 (55H)	0.75	1.00	25	25		3300	3100	3000	2950	2900	2800	2500	2400	2200	1700	1500	1100	750

Material of Construction

Impeller : H.T. Brass
 Motor Body : Aluminum
 Shaft : SS Shaft

Features

- Withstand wide voltage fluctuation from 180 to 255 volts.
- Thermal overload protector (TOP) prevents motor burning.
- High quality aluminum body, Light weight pump for easy handling.

Applications

- Water supply for domestic use in Bungalows, Apartments, Hotels, Hospital, Farm house, etc.
- Useful in Home presser booster system, Lawn sprinklers.



SHALLOW WELL PUMP

Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		Discharge in LPH	Head in Meter													
	Kw	HP	Suc.	Del.		6	9	12	15	18	21	24	27	30	33	36	40		
LSW 05	0.37	0.50	25	25		3200	3150	3100	3050	2950	2650	2000	1500	1000	500	0	0		
LSW 10	0.75	1.00	25	25		3500	3400	3350	3300	3200	3150	3050	2500	2050	1550	1100	400		

Material of Construction

Motor Body : Aluminum

Features


- Withstand wide voltage fluctuation from 180 to 255 volts
- High quality Cast iron body.
- Light weight pump for easy handling.

Applications

- Water supply for domestic use in Bungalows, Apartments, Hotels, Hospital, Farm house, etc.
- Useful in Home presser booster system, Lawn sprinklers.

LMS - SLOW SPEED PUMP

(1440 RPM)



Technical Data :

Model Name	Motor Rating		Pipe Size (mm)		Discharge in LPH	Head in Meter													
	Kw	HP	Suc.	Del.		6	9	12	15	18	21	24	27	30	33	36	40		
LMS 05	0.37	0.50	25	25		3250	2900	2650	2300	2000	1700	1500	1300	600	0	0	0		
LMS 10	0.75	1.00	25	25		4100	3900	3700	3400	3100	2900	2650	2400	2100	1900	1700	1250		

Material of Construction

Motor Body : Cast Iron

Features

- Withstand wide voltage fluctuation from 180 to 255 volts
- High quality Cast iron body.
- Light weight pump for easy handling.

Applications

- Water supply for domestic use in Bungalows, Apartments, Hotels, Hospital, Farm house, etc.
- Useful in Home presser booster system, Lawn sprinklers.